

MTM - MTM/HP



from 240 to 360 HP



D16 in

- STONE CRUSHER
- ROCK GRINDER

- STABILIZER
- ASPHALT SHREDDER

FOR TRACTORS FROM 240 TO 360 HP WITH A WORKING DEPTH UP TO 16 IN AND VARIABLE GEOMETRY CRUSHING CHAMBER.

The MTM is a multipurpose machine designed and built for use with medium-high-power tractors with the same technical features as the larger MTH model, used to stabilize soil, grind rock slabs, crush stones, and shred asphalt with a maximum working depth of 16 in. Compact dimensions and extreme maneuverability allow to work on limited surfaces that are difficult for self-propelled units to reach. They can also be easily transported from one jobsite to another. The variable geometry crushing chamber is a highly

innovative solution to provide excellent crushing results. The mobile rotor, which can be hydraulically adjusted from the tractor cab, allows the volume of the crushing chamber to increase according to the working depth. Limited traction stress means reduced fuel consumption, increased operating speed and therefore, increased savings in terms of time and operating costs. The HARDOX® counter knife and rear-mounted grill system ensure that the final product is the correct size.



| MODEL | Tractor HP | PTO (rpm) | Working width (in) | Total width (in) | Weight (lbs) | ROTOR G/3 | | | ROTOR R | | |
|------------|------------|-----------|--------------------|------------------|--------------|--------------------|--------|--|--------------------|--------|--|
| | | | | | | Working depth (in) | | No. teeth/type G/3 + STC/3/FP + STC/FP | Working depth (in) | | No. teeth /type R + R/HD + STC/3/FP + STC/FP |
| | | | | | | Max. 1 | Max. 2 | | Max. 1 | Max. 2 | |
| MTM 200 | 240-300 | 1000 | 80 | 98 | 12,570 | 10 | 16 | 92+4+4 | 9 | 16 | 126+20+4+4 |
| MTM 225 | 240-300 | 1000 | 90 | 107 | 13,500 | 10 | 16 | 104+4+4 | 9 | 16 | 144+20+4+4 |
| MTM/HP 200 | 300-360 | 1000 | 80 | 98 | 12,570 | 10 | 16 | 92+4+4 | 9 | 16 | 126+20+4+4 |
| MTM/HP 225 | 300-360 | 1000 | 90 | 107 | 13,500 | 10 | 16 | 104+4+4 | 9 | 16 | 144+20+4+4 |

Max.1: with rotor only Max.2: maximum depth
This information refers to the machine equipped as standard. The technical data in this catalog may be altered without prior notice.



INNOVATIVE SOLUTION



TOUGH

WELDOX® steel frame and guards in made of HARDOX® steel to ensure the utmost resistance to wear and tear.



EASY TO HANDLE

With its compact size, the machine can work in tighter spaces that are difficult for self-propelled units to reach.



EFFICIENCY

The variable geometry crushing chamber, protected by HARDOX® covering, ensures excellent grinding results.



PRECISION

The HARDOX® counter knife and rear-mounted grill system ensure that the final product is the correct size.