



from 160 to 240 HP



Ø 12 in max

## FORESTRY MULCHER WITH FIXED TOOTH ROTOR.

A professional mulcher with fixed teeth for processing material up to 12" diameter. The UMM/DT offers a compact size that makes it easy to handle while mulching, especially for difficult applications like steep slopes. This mulcher features a heavy duty frame with protection integrated for the cylinder and hydraulic link. It also features interchangeable counter-blades for easy maintenance and replacement, as well as a centralized greasing hub, push frame with ripper, and adjustable linkage for mounting to a 3 point hitch.

STANDARD EQUIPMENT
PTO shaft with cam clutch
Gearbox with freewheel
Transmission with belts in XPB
Hydraulic hood
Forged and hardened interchangeable counter-blades
Interchangeable inner antiwear plates in Hardox®
Adjustable skids
Enclosed machine body
Centralized greasing hub
Hydraulic top link
Z style self ranging system of the PTO drive shaft/gearbox

Hydraulic hoses integrated in the frame
Cylinder protection
Dual row protection chains

OPTIONS
Third row of interchangeable forged and hardened counter-blades
W style self aligning device between PTO drive shaft/gearbox
Mechanical push frame
Hydraulic push frame
Extra ripper for push frame
Special skids to go underground
Multiple tooth options



FOR THOSE SEEKING THE TOP  
WITH MEDIUM POWER TRACTORS

## FEATURES

**Cylinder protection**  
to prevent cylinder damage

**Reinforced hood**  
helps to provide a finer product

**Forged and hardened interchangeable counter-blades**  
for the longest working life while providing a finer product

**Z style self ranging system of the PTO drive shaft/gearbox**  
helps keep the correct operating angle between the PTO shaft and the power take-off

**Centralized greasing hub**  
allows easy maintenance

## MAIN OPTIONS

**1 Third row of counter-blades**  
processes material to a finer finished product

**2 W style self aligning device between PTO drive shaft/gearbox**  
allows the mulcher to work in several angles without damaging the PTO

**3 Mechanical/hydraulic push frame**  
guides and pushes material away from carrier

**4 Additional ripper for push frame**  
helps with the positioning of standing material while mulching

MODEL	Engine (HP)		PTO (rpm)	Working width (in)	Total width (in)	Weight (lbs)	Max shredding diameter (in)	No. teeth type C/3 + C/3/SS	No. teeth type I + C/3/SS
	min	max							
UMM/DT 200	160	240	1000	81	97	4916	12	42+2	58+2
UMM/DT 225	170	240	1000	91	106	5467	12	46+2	66+2
UMM/DT 250	180	240	1000	100	116	5622	12	52+2	74+2

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.